

KE-100 Duet

with Two Components

KE-100 Duet is a high performance Epoxy based two component tile grout. Easy to use and suitable for all wall and floor tiles, marble and natural stone.



Water Resistant



Stain Free



Bacteria Resistant



Fast Curing




Easy to Clean



AVAILABLE IN
18
COLOURS

Plain Colours


1KG & 5KG PACK SIZE



CREMA




CHAMPAGNE



LIGHT GREY



AUTUMN YELLOW



ALMONDO



SANDALWOOD




LIGHT TAUPE



BRICK RED




CHOCOLATE



LAUREL GREEN



AQUA



SEA BLUE



NAVY BLUE



TURQUOISE BLUE



DARK GREY



COFFEE BEAN

Elite Plain Colours

1KG & 5KG PACK SIZE



SNOW WHITE




BLACK

KE-100 Glitter

Glitter Effects are specifically designed to enhance both aesthetics and performance. It is suitable for use with ceramic tiles, vitrified tiles, glass mosaic tiles, designer tiles and natural stone.




Combine any of our 18 grout colours with 3 special glitter effects:



GOLD



SILVER



COPPER

*Shelf Life for all KE-100 Duet Grouts is 1 Year in Dry, Unopened Condition

KE-100 Epoxy Grout

KE-100 Epoxy Grout is formulated with 3-component epoxy resin, which offers a high degree of resistance to chemicals, abrasion and impact.

KE-100 Epoxy Grout is available in a range of 18 colours. Refer to the section under KE-100 Duet for colour range.



*KE-100 Epoxy Grout has a shelf life of 1 year in a dry, unopened condition. It is available in a 1KG and 5KG Pack.

Coverage Chart

Tile Size X Thickness	Joint Width						
	2 mm	3mm	4 mm	6 mm	8 mm	10 mm	12 mm
100x100x3	284	177	133	90	68	55	46
150x150x4	296	198	143	100	75	61	51
200x150x5	289	181	136	91	69	55	46
150x300x6	283	175	132	88	66	53	44
300x300x6	394	263	198	132	100	80	67
450x300x7	405	270	202	135	101	81	68
600x450x8	506	337	253	169	127	101	85
600x600x8	591	394	295	197	148	119	99
600x900x11	515	343	258	171	129	103	86
900x900x12	590	393	295	197	148	118	99

Coverage: Approximate sq. ft. coverage per # 1 unit (5KG) of Gresbond.
As per the actual site the consumption vary accordingly. These figures are for indicative purposes.

grès**bond**
by *Kajaria*

Premium Unsanded Grout

Gresbond Premium Unsanded Grout is a blend of portland cement, graded aggregates, polymer fortifiers and colour-fast pigments. It is designed for 1 mm to 3 mm joint widths and compatible with a wide range of tile and stone materials including ceramic, vitrified, glass mosaic, granite, marble, engineered stone, terrazzo, and brick.



Weather Resistant



Smooth Finish




Easy Maintenance



Non Shrinking



Hard and Durable



AVAILABLE IN
20*
COLOURS

*Premium Unsanded Grout has a shelf life of 1 year in dry, unopened pouches. It is available in a 1KG Pack.

*Refer section under KE-100 Duet for colour list

Coverage Chart

Coverage (in sq. ft.): Approximate sq. ft. coverage per 1 kg unsanded grout.

Tile Size x thickness (in mm)	1 mm	2 mm	3 mm
100 x 100 x 3	143	72	48
150 x 150 x 4	161	81	54
200 x 150 x 5	147	74	49
150 x 300 x 6	143	86	47.8
300 x 300 x 6	215	71.6	71
450 x 300 x 7	220.5	110.4	73.7
600 x 450 x 8	275.5	137.9	92
600 x 600 x 8	321	161	107
600 x 900 x 11	280.4	140.3	107
900 x 900 x 12	321.3	160.8	107.2

Mixing Ratio: Use about 400 ml of water or KGA-01 grout admix per 1 kg of Gresbond Premium Unsanded Grout.

KGA-01 Premium Grout Admix

Gresbond Premium Grout Admix KGA-01 is a polymer based liquid admixture specially designed for use in combination with Kajaria Grouts. This additive creates a dense, colourfast grout suitable for indoor & outdoor use. It enhances performances and prevents moisture from seeping behind tiles.



No Water Leakage



Shock & Impact Resistant



Weather Resistant



Seamless Look



*Premium Grout Admix KGA-01 has a shelf life of 1 year. It is available in a pack size of 400ml (Carton of 10 bottles - 4000ml).

KAJARIA DISPLAY CENTRES / REGIONAL OFFICES

NORTH

CHANDIGARH:

Phones: +91-172-4631418, 4631415
Email: chandigarh@kajariaceramics.com

DEHRADUN:

Phones: 0135-2675329
Email: dehradun@kajariaceramics.com

JAMMU:

Mob: +91 7827993481, Phone: 7966728
Email: jammu@kajariaceramics.com

JAIPUR:

Phones: 0141-4910941, 2220244
Email: jaipur@kajariaceramics.com

LUDHIANA:

Phones: +91-161-4649002
Email: ludhiana@kajariaceramics.com

LUCKNOW:

Phones: 0522-4029181, Mob: 9837906663
Email: lucknow@kajariaceramics.com

VARANASI:

Phones: 0542-2500483, Mob: 9005092402
Email: varanasi@kajariaceramics.com

EAST

PATNA: (Regional Office)

Phone: +91 93347 91993

KOLKATA: (Regional Office)

Phones: +91-33-40231111
Email: kol@kajariaceramics.com

CENTRAL

RAIPUR: (Regional Office)

Phone: +91 7714060427
Email: raipurdepot@kajariaceramics.com

INDORE: (Regional Office)

Phones: 0731-4068839, 97525 93462
Email: indore@kajariaceramics.com

For Trade Enquiries, please contact: info@gresbondbykajaria.com

gresbond
by Kajaria



GROUTS



NORTH & EAST

Application Instructions



Step 1

Ensure adhesive is fully set before grouting. Clean joints of debris and adhesive then fill movement joints with flexible sealant.



Step 2

Mix parts A and B in a clean vessel until uniform. Slowly add part C (coloured filler powder) for a smooth, slump-free paste. Pour the mixed grout onto the work area immediately.



Step 3

Using a hard rubber float, press KE-100 Epoxy Grout into joints until fully filled. Work in small sections, removing excess grout continuously. Hold the float diagonally to the grout lines and scrape off excess.



Step 4

Let joints stiffen for 15-30 minutes. Clean rustic/matte tiles with a grout scrubber and smooth tiles with a damp sponge/cloth. Scrub grout lines in circular, diagonal motions. After 12-24 hours, clean the surface with soapy water to remove epoxy stains.

Storage and Shelf Life:

12 months when stored in dry condition.

FOR MORE INFORMATION VISIT
www.gresbondbykajaria.com