

TC1 Tile Cleaner

PRODUCT DESCRIPTION:

GRESBOND TC1 Tile Cleaner is a powerful, fast-acting, acid-based solution designed for the effective removal of dirt and stains from floor and wall tiles. Ideal for daily maintenance, TC1 ensures your tiles remain spotless and gleaming



FEATURES / BENEFITS	SUBSTRATES
New and improved formula	Vitrified tile
Suitable for all tile surfaces	Ceramic tile
Ready to use	Glass Mosaic Tile
Fast-acting	Unglazed ceramic tiles
Ideal for interior and exterior use	Porcelain tile

Mixing and Application: For Interior & Exterior Use

- Shake the container well before opening.
- Dilute 1 part of cleaner with 4 parts clean water. For heavily soiled areas, use undiluted.
- Pour GRESBOND TC1 on the stained surface.
- Let it stand for 4-5 minutes to react with the stain.
- Scrub the surface with a pad, adding more GRESBOND TC1 if it dries.
- Rinse with water and repeat if necessary.
- For regular maintenance, dilute as needed to clean tiles.

APPEARANCE	PALE RED LIQUID
Specific gravity	1.02
рН	5-6

• PACKAGING : GRESBOND TC1 tile cleaner is packaged in sealed bottle of 750ml.



CAUTIONS:

- Protect neighbouring surfaces, including wood, carpet, metal, landscaping and other areas.
- Acids, even mild ones, can etch, lighten, or alter tile colour depending on the tile's quality.
- Avoid contact with metals.
- Do not mix with ammoniated cleaners; harmful fumes may result.
- Allow new epoxy grout to cure according to the manufacturer's specifications before using GRESBONDTC-1.
- Contact with cement-based grouts may affect their performance and colour.
- Wear gloves, a nose cover, and eye protection while using this product.
- Keep out of reach of children

COVERAGE :

• Coverage depends on the porosity of surface and intensity of stains on the surface

STORAGE INSTRUCTIONS :

- Close the container tightly after use to prevent contamination and solvent loss.
- Store only in the original container.
- Keep in a temperature range of 4°C to 40°C

LIMITATIONS :

Do not use on porous marble or similar natural stone surfaces

MAINTENANCE :

- Avoid general cleaning chemicals on sealed surfaces.
- Clean with plain, soft water.

Note: All impregnating sealers and cleaners are maintenance products. Surfaces treated with sealers require careful upkeep.

Customer Care

Kajaria Ceramics Limited

J1/B1 (Extn.), Mohan Co-op Industrial Estate (Opp. Badarpur Thermal Power Station), Mathura Road, New Delhi - 110 044 Phone: +91-11-2694 6409 Fax: +91-11-2694 6407, 2694 9544 | Email: info@kajariagresbond.com